

Pertasol Spesification

Typical Spec. Range Pertasol CA

No	Parameter	Unit	Spesification		Methods
			Min	Max	
1	SG 60/60 °F		0,685	0,724	ASTM D-1298
2	Distilation:				
3	2.1 Initial Boiling Point	°C	40	-	ASTM D-86
4	2.1 End Boiling Point	°C	-	153	
5	Aromatic	% vol	4		ASTM D-1319
6	Color (Saybolt)		25		ASTM D-156
7	Copper Corrosion 2 hours/100 °C	-	No. 1 strip		ASTM D-130
8	Doctor test	-	Negative		ASTM D-4952
9	Odor	-	Marketable		

Typical Spec. Range Pertasol CB

No	Parameter	Unit	Spesification		Methods
			Min	Max	
1	SG 60/60 °F		0,7662	0,7240	ASTM D-1298
2	Distilation:				
3	2.1 Initial Boiling Point	°C	95	-	ASTM D-86
4	2.1 End Boiling Point	°C	-	192	
5	Aromatic	% vol	16		ASTM D-1319
6	Color (Saybolt)		25		ASTM D-156
7	Copper Corrosion 2 hours/100 °C	-	No. 1 strip		ASTM D-130
8	Doctor test	-	Negative		ASTM D-4952
9	Odor	-	Marketable		

Typical Spec. Range Pertasol CC

No	Parameter	Unit	Spesification		Methods
			Min	Max	
1	SG 60/60 °F		0,685	0,724	ASTM D-1298
2	Distillation:				
3	2.1 Initial Boiling Point	°C	120	-	ASTM D-86
4	2.1 End Boiling Point	°C	-	250	
5	Aromatic	% vol	16		ASTM D-1319
6	Color (Saybolt)		25		ASTM D-156
7	Copper Corrosion 2 hours/100 °C	-	No. 1 strip		ASTM D-130
8	Doctor test	-	Negative		ASTM D-4952
9	Odor	-	Marketable		