

LAWS 2 & 5 Specification

LAWS 2

No	Analysis	Method	Unit	Spesification
1	Appearance	C-042/PL2200/2014-S0		Clear
2	Specific Gravity at 60/60 deg. F	ASTM D-4052-11		0.770 - 0.8100
3	Colour Saybolt	ASTM D-6045-09		Min. +25
4	Flash Point	IP-170	deg C	Min. 32
5	Distillation :			
	IBP	ASTM D-86	deg C	Min. 143
	FBP	ASTM D-86	deg C	Max. 210
8	Aniline Point	ASTM D-611-07	deg C	40-45
9	Copper Strip Corrosion, 3 hrs/100 deg. C	D-130-10	Class	Max. No. 1
10	Doctor test	IP-30		Negative
11	Aromatic Content	ASTM D-1319	% vol	15-30

LAWS 5

No	Analysis	Method	Unit	Spesification
1	Appearance	C-042/PL2200/2014-S0		Clear
2	Specific Gravity at 60/60 deg. F	ASTM D-4052-11		0.770 - 0.8100
3	Colour Saybolt	ASTM D-6045-09		Min. +25
4	Flash Point	IP-170 / ASTM D-93	deg C	To be reported
5	Distillation :			
	IBP	ASTM D-86	deg C	Min. 130
	FBP	ASTM D-86	deg C	Max. 210
8	Aniline Point	ASTM D-611-07	deg C	53-58
9	Copper Strip Corrosion, 3 hrs/100 deg. C	D-130-10	Class	Max. No. 1
10	Doctor test	IP-30		Negative
11	Aromatic Content	ASTM D-1319	% vol	Max. 12