

## Paraffinic Oil Specification

### Paraffinic Oil 60

No	Specification	Method	Min	Max
1	Flash Point COC °F	ASTM D - 92	400	-
2	Pour Point °F	ASTM D - 97	-	8
3	Refractive Index at 20°C	ASTM D - 1218	1,4750	1,4815
4	Viscosity Gravity Constant	ASTM D - 2501	0,8095	0,8205
5	Colour ASTM, 1% dilution	ASTM D - 1500	-	0,5
6	Specific Gravity at 60/60°F	ASTM D - 1298	0,8460	0,8735
7	Viscosity Kinematic at 210°F Cst	ASTM D - 445	4,5	5,0
8	Anline Point °C	ASTM D - 611	96	103

### Paraffinic Oil 95

No	Specification	Method	Min	Max
1	Flash Point COC °F	ASTM D-92	410	-
2	Pour Point °F	ASTM D-97	-	15
3	Refractive Index at 20°C	ASTM D -1218	1,4800	1,4900
4	Viscosity Gravity Constant	ASTM D-2501	0,8100	0,8330
5	Colour ASTM, 1% dilution	ASTM D-1500	-	0,5
6	Specific Gravity at 60/60°F	ASTM D-1298	0,8760	0,8850
7	Viscosity Kinematic at 210°F Cst	ASTM D-445	6,9	7,6
8	Anline Point °C	ASTM D-611	100	109

The specification above is valid when printed, for actual specification please contact Pertamina